# **HMC1050**

### 3Vpp Optical Modulator Driver / Wideband Amplifier, DC - 30 GHz

**Product Details** 

Request Data Sheet ECCN: EAR99

Quality & Reliability

Waffle-Pak & Gel-Pak

Press & Media

Featured Article

**Life Cycle Status** 

Production,
Recommended for
New Designs

Data Rate (Gbps)	Function	Gain (dB)	Group Delay Variation (ps)	Additive Jitter (ps)	Output Voltage Max. (Vp-p)	Package
32	3Vpp Optical Modulator Driver, with Peak Detect	14	±5	0.3	3	Chip

### Features

- Low DC Power Dissipation, 0.36W for 2.8Vpp swing @ 6V supply
- Integrated peak-detect function

No Image

Available

- 14.8 dB Gain @ 16 GHz
- +15 dBm typical saturated output power
- Low Additive RMS Jitter, <300 fsec
- Rise and Fall Times 12 ps
- Small Die Size:

1.71 x 1.35 x 0.10 mm

## **Typical Applications**

- Up to 32Gbps optical modulator driver
- Test and Measurement Instrumentation
- Microwave Radio & VSAT
- Military & Space
- Up to 32Gbps pre-driver or receiver block

# OND 1 18 17 16 15 14

**Functional Diagram** 

# **General Description**

The HMC1050 is a GaAs MMIC PHEMT Distributed Amplifier die which operates between DC and 30 GHz. The amplifier provides 14 dB of gain, and +14 dBm of output power at 1 dB gain compression. HMC1050 has a wide supply (Vdd) operating range from +5V to +7V.

Integrated Peak-Detect Function enables the output power stability for calibration and field monitoring. The HMC1050 amplifier I/Os are internally matched to 50 Ohms facilitating integration into Mutli-Chip-Modules (MCMs). 2.80 Vpp output voltage swing can be obtained with 500mVpp input when stimulated with 32Gbps 2<sup>31</sup>-1 PR BS NRZ data.

The HMC1050 is suitable for a variety of wideband electronic warfare systems and test & measurement applications including NRZ applications up to 32 Gbps. The HMC1050 is capable of driving Mach- Zehnder optical modulator with electrical NRZ data. In addition, the HMC1050 may also be used as a predriver or a receive gain block.

Hittite Microwave (Chelmsford, MA USA) is an <a href="ISO 9001:2008">ISO 9001:2008</a> and <a href="AS9100:2009">AS9100:2009</a> Certified Designer and Manufacturer © 2000 - 2014 Hittite Microwave Corporation | <a href="Legal Notice">Legal Notice</a> | <a href="Privacy Policy">Privacy Policy</a> 978-250-3343 | <a href="mailto:sales@hittite.com">sales@hittite.com</a>