Material			High Conductivity	1					
			Seamless Copper Tube	_			_	.63 R Ref	
Plating			Electro-Tin						
Wire Size			3/0 AWG	<u> </u>	<u>⊢</u> (∰) .				PANDUIT
Wire Type			Stranded Copper; Class B: Compact, Compressed or Concentric, Class C: Concentric	.96±.04	PANDUIT	3/0 STR CU LCC3/0-12WH			
Wire Strip Length		h	1-9/16 in.						ORANGE DIE P50 (14)
Stud Size			1/2 in.		63±.04	.75±.0	2	C31 00 D14	
UL Listed Wire Connector			Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts.		001.04	./ 51.0	2	53±.02 DIA (2) PLS	Color coded barrel marking
UL Temperature Rating		1	90° C				Bevele	d wire entry——	.64±.01
C.S.A Certified Wire Connector			Yes						.51±.01
Panduit Color Code on Barrel		ode	ORANGE				1.5	50±.04	
Panduit I on Barre		ex No.	P50						
Alternate Die Inde: on Barrel	x No. ()		(14)		Wire insp	ection	n window	45°±.	1.85 REF 5°
	CE	RTIFIEC	USTED .13± Wire Connector	:.01			4.38 REF		-
								CORP.	TINLEY PARK, ILLING
0 7/02 SAB DRL RELEASE			0 10341		0341	Copper Lug - Two-Ho	-X 1 Window, 45° Angle Tong		
V DATE	BY	СНК	DESCRIPT			ECN	SCALE	DRAWING NO / CAD FI	ı F